

# EG704T

Low Profile Goggle



Low Profile Goggle

Part Lens

EG704T •••  Clear Anti-Fog

- Low profile, modern sport design with anti-glare frame.
- Direct ventilation prevents fogging.
- Adjustable elastic band and soft PVC frame.
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection.

## GENERAL SPECIFICATION

Bridge: 21mm

Closest Point Between Lens: 18mm

Lens Base: 6 Curve

Lens Size Diagonal: 82mm

Lens Size Vertical: 52mm

Lens Thickness: 2mm - 2.2mm

Overall Width (Hinge-Hinge): 148mm

PD: 64mm

Weight: 35gm

## PACKAGING

Polybag: 1pc

Inner Box: 12 pcs

Case: 144 pcs

## EG704T

COMPONENT	MATERIAL	FEATURES
Nose Piece	N/A	Integrated with PVC Frame
Frame	PVC	Low-profile frame design
Strap	N/A	Elastic Strap
Lens	Polycarbonate	6 base curve
Side Shields	N/A	Integrated with PVC Frame
Connector	Nylon	Thin and modern design

PART	LENS	LENS MARKING	FRAME MARKING
EG704T	 Clear (Anti-Fog)	2C - 1.2 P 1 BT CE	P EN166 BT CE

**LENS MARKING****Code (field of use):**

2 or 3: UV Filter  
5 or 6: Solar Filter

**Color Perception:**

C: Unimpaired color perception

**Protection Class:**

1.2 to 6: Degree of visible light filtration

**Optical Class:**

1: High optical quality / No optical distortion

**Mechanical Strength:**

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s  
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s  
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s  
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

**Symbols:**

P: Manufacture Indication  
N: Filter with Anti-Fog features  
CE: European Standard

**FRAME MARKING****Symbols:**

CE: European Standard  
P: Manufacture Indication  
EN166: CE specification for protective eyewear

**Mechanical Strength:**

F: Low energy impact  
B: Medium energy impact  
BT: Medium energy impact at extreme temperatures

**Protection Class:**

3: Protection against liquid droplets  
4: Protection against large dust